





| Dimensions  |            |
|---|------------|
| Width (external)  | 1196.00 mm |
| Depth (external)  | 616.00 mm  |
| Height (external)   | 1968.00 mm |
| Width (internal)  | 1050.00 mm |
| Depth (internal)  | 524.00 mm  |
| Height (internal)   | 1742.00 mm |
| The available internal dimensions can vary depending on the interior equipment package. |            |

| Weight / Load                        |              |
|--------------------------------------|--------------|
| leight without interior equipment    | 420 kg       |
| stributed load                       | 528.00 kg/m² |
| aximum load                          | 600 kg       |
|                                      |              |
| ntilation                            |              |
| traction air                         | 75 DN        |
| inimum exhaust air quantity 10 times | 10 m³/h      |
|                                      | 5 Pa         |

| Colouring / Surface finish   |                                     |
|------------------------------|-------------------------------------|
| Body colour code             |                                     |
| Body colour                  | Laboratory white (sim. RAL<br>9016) |
| Body surface finish          | plain                               |
| Door / Drawer colour code    |                                     |
| Door / Drawer colour         | Laboratory white (sim. RAL<br>9016) |
| Door / Drawer surface finish | plain                               |
|                              |                                     |

| General Information      |          |  |
|--------------------------|----------|--|
| Number of doors          | 2        |  |
| Door opening angle       | 89.00°   |  |
| Interiour grid dimension | 32 mm    |  |
| Depth with open doors    | 1173 mm  |  |
| Customs tariff number    | 94032080 |  |

















Safety storage cabinet S-CLASSIC-90 Model S90.196.120, laboratory white (sim. RAL 9016)

Safe and approved storage of flammable hazardous substances in working areas

## **Function / construction:**

- Robust construction and longevity: triple hinged door, body made of powder-coated sheet steel, safety elements assembled outside the cabinet for increased protection against corrosion
- **No unauthorised use:** doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system