

## Model S90.129.060.WDAS






















Safe and approved storage of flammable hazardous substances in working areas

## **Function / construction:**

- Robust construction and longevity: triple hinged door, body made of powder-coated sheet steel, safety elements assembled outside the cabinet for increased protection against corrosion
- User-friendly and safe (model .WDAS): door open arrest system, convenient and safe removal or storage of containers
- **No unauthorised use:** door lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system



Dimensions	
Width (external)	596.00 mm
Depth (external)	616.00 mm
Height (external)	1298.00 mm
Width (internal)	450.00 mm
Depth (internal)	524.00 mm
Height (internal)	1072.00 mm
The available internal dimensions can vary depending on the in	nterior equipment package.

Weight / Load	
Weight without interior equipment	170 kg
Distributed load	799.00 kg/m²
Maximum load	600 kg
Ventilation	
Ventilation Extraction air	75 DN
	75 DN 3 m³/h

Colouring / Surface finish	
Body colour code	
Body colour	Laboratory white (sim. RAL 9016)
Body surface finish	plain
Door / Drawer colour code	
Door / Drawer colour	Laboratory white (sim. RAL 9016)
Door / Drawer surface finish	plain

General Information	
Number of doors	1
Door opening angle	89.00°
Interiour grid dimension	32 mm
Depth with open doors	1134 mm
Customs tariff number	94032080

Front view Side view

